



M-298i

Hardware Performance

Firewall	22,000 Mbps
VPN	12,000 Mbps (SSL Multi-Tunnel) 16,000 Mbps (IPSec Multi-Tunnel) 16,000 Mbps (Wireguard Multi-Tunnel)
IDS	8,000 Mbps
IPS	3,000 Mbps
Anti-Malware	1,300 Mbps 2,200 Requests /s
Content Filtering	1,230 Mbps 2,000 Requests /s
Email protection	468,000 emails /hr
WAF	1,800 Mbps 7,000 Requests /s
Anti-DDoS	800 Mbps 4,000 Requests /s 450,000 Attacks /s

Hardware Specifications

Processor	64bit, 4.4GHz x 6 Performance Cores 64bit, 3.3GHz x 4 Efficiency Cores
RAM	2 x 16GB, 3200MHz DDR4
Storage	4TB HDD
Networking	6 x 2.5Gb RJ45
Power Supply	90~264V (47Hz-63Hz) AC
Chassis	1u Rackmount
I/O Interface	1 x RJ45 management console 2 x USB 3.0
Dimensions	430(w) x 44.5(h) x 370(d) mm
Weight	6.11kg
Optional Add-on	4 x 1Gb RJ45 LAN Port <i>or</i> 4 x 10Gb SFP+ LAN Port

network-box.com

The trademarks, including but not limited to "Network Box" and the curly "N" device, are either trademarks or registered trademarks of Network Box Corporation Limited. Other trademarks and product names used in this publication are for identification purposes only, and may be the trademarks of their respective companies. Features and specifications are subject to change without notice. Benchmarking is performed with representative data, on a function by function basis. Weights and measurements are approximate only. Actual models may vary in appearance to the illustration and photographs provided. All specifications are subject to change without notice.

